

TECHNICAL DATA.


MODEL SJD2EXE

Supreme Jet Dry Executive II

Automatic Hand Dryer 1.0kW







Height Recommendations

(From floor to top of the mounting plate)

Female and male washrooms 90cm

Disabled persons 75cm

571

P.O Box427, Cambridge,

New Zealand

Tel: 64 7 823 5790 | Fax: 64 7

office@splwashrooms.co.nz

www.splwashrooms.co.nz

Motor Brushless Electronic Commutated - Two Speed

Sound levels 55dBA @ 1.0m

Power 1000 Watts max

Element Nil

Rating 4 amps @ 240 V AC IP33

Maximum Airflow 155m/sec

Cover ABS/ Polycarbonate antimicrobial impregnated

Dimensions/Weight 660H x 330W x 230D mm

Warranty Supreme 36 month limited warranty

Standards Complies with New Zealand/ Australian standards

SAMPLE SPECIFICATION

Supreme Jet Dry Executive II

General

Scope:- Supply and install Supreme Jet Dry automatic hand dryer as shown on the plans

Materials

Primary materials:- Supreme Jet Dry Hand Dryer made from ABS/ Polycarbonate antimicrobial impregnated.

Workmanship

Using the mounting template supplied, position the mounting bracket and affix to the wall using the appropriate fixing for the type of wall.

The electrical connection can be made by fixed wiring of the correct cross section back to an isolating switch in a convenient location all as per local electrical codes of practice.

Hook top of dryer on to mounting bracket and secure the bottom of the machine with a single screw into the wall. The screw position is accessible after removal of the drip tray as per (5) on fixing template.

Liven machine and test operation.

Completion

Leave work clean, remove all trade rubbish from the site and leave the hand dryer cleaned and in working order.

Pass over warranties/ manuals/ cleaning and maintenance instructions to the principal.

We reserve the right to alter specifications and design without prior notice