



# Coreline Slim Batten

## BN126C LED60S/840 PSU L1500

Coreline Slim Batten, 46 W, 6000 lm, 4000 K

The new Philips Coreline slim batten offers exceptional value. It is Perfect for your everyday lighting installations. Available in 3 standard sizes, and 2 CCTs to provide flexibility to customer.

### Product data

<b>General Information</b>		<b>Temperature</b>	
Light source engine type	LED	Ambient temperature range	-20 to +40 °C
CE mark	CE mark	<b>Controls and Dimming</b>	
<b>Light Technical</b>		Dimmable	No
Luminous Flux	6,000 lm	Control interface	-
Correlated Color Temperature (Nom)	4000 K	<b>Mechanical and Housing</b>	
Luminous Efficacy (rated) (Nom)	105 lm/W	Housing Material	Steel
Color rendering index (CRI)	>80	Optical cover material	Polycarbonate
Light source color	840 neutral white	Housing Color	White RAL 9003
Optical cover type	Polycarbonate Diffuser	Optical cover finish	Opal
<b>Operating and Electrical</b>		Overall length	1,450 mm
Input Voltage	220 to 240 V	Overall width	65 mm
Line Frequency	50 or 60 Hz	Overall height	65 mm
Power Consumption	46 W	Dimensions (Height x Width x Depth)	65 x 65 x 1450 mm
Power Factor (Fraction)	0.9	<b>Approval and Application</b>	
Number of products on MCB of 16 A type B 30		Ingress protection code	IP20/40 [Finger-protected, Emitting surface]
		Mech. impact protection code	IK04 [0.5 J standard plus]

Coreline Slim Batten

Protection class IEC	Safety class I
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	BN126C LED60S/840 PSU L1500
Full product name	BN126C LED60S/840 PSU L1500
Full product code	692382863855999

Local code description	BN126C60840PL15
Order code	911401899180
Material Nr. (12NC)	911401899180
Local order code	BN126C60840PL15
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6923828638559
Numerator - Packs per outer box	6
EAN/UPC - Case	6923828638610

Dimensional drawing

