## PHILIPS CorePro

## LED PL-C 6.5 & 8.5 W 2-pin

- First A-branded lamp-for-lamp replacement for conventional PL-C lamps with 2-pin sockets (EM-control gear).
- Low energy consumption (> 60% energy saving) and long lasting (twice as long lifetime than fluorescent).
- Cost effective retrofit option for downlight luminaires in public buildings, corridors and hallways.
- Perfect for office, retail or hospitality applications.
- Suitable for horizontal lamp fittings.

## What's new:

- In two color temperatures (3000 & 4000 K) and two wattage positions for G24d-2 and G24d-3 socket holders.
- Efficiency up to 100 lm/W.
- < 2 years pay-back, at affordable initial price point as alternative for LED Downlight luminaires.
- Rotating end-caps, to rotate light in the ideal direction.







non-dimmable





G24d-2 & G24d-3



Final information

PHILIDS

Product description	Dimensions	System Wattage	Equivalent	Colour temp	Lumen output	Operation	CRI	12NC
	mm	W	W	K	Im			
CorePro LED PLC 6.5W 830 2P G24d-2	33x147	6.5	18	3000	600	Electro Magnetic	80	929001201402
CorePro LED PLC 6.5W 840 2P G24d-2	33x147	6.5	18	4000	650	Electro Magnetic	80	929001201502
CorePro LED PLC 8.5W 830 2P G24d-3	33x170	8.5	26	3000	900	Electro Magnetic	80	929001201202
CorePro LED PLC 8.5W 840 2P G24d-3	33x170	8.5	26	4000	950	Electro Magnetic	80	929001201302