

## SCAME Connectors



Socket Front View



### IP67 OPTIMA Connector

Code	Rating	Pins	Earth Position
<b>110v YELLOW</b>			
<b>318.1640</b>	16 Amp	2 P + E	4H
<b>240v BLUE</b>			
<b>318.1643PTR</b>	16 Amp	2 P + E	6H Ins. Perforation
<b>318.1643TR</b>	16 Amp	2 P + E	6H
<b>326.1643</b>	16 Amp	2 P + E	6H (Right Angle)
<b>318.3243</b>	32 Amp	2 P + E	6H
<b>318.6343</b>	63 Amp	2 P + E	6H
<b>415v RED</b>			
<b>318.1646</b>	16 Amp	3 P + E	6H
<b>326.1646</b>	16 Amp	3 P + E	6H (Right Angle)
<b>318.1647</b>	16 Amp	3 P + N + E	6H
<b>318.3246</b>	32 Amp	3 P + E	6H
<b>318.32464</b>	32 Amp	3 P + E	3H* (Reefer)
<b>318.3247</b>	32 Amp	3 P + N + E	6H
<b>318.6346</b>	63 Amp	3 P + E	6H
<b>318.6347</b>	63 Amp	3 P + N + E	6H
<b>318.12546</b>	125 Amp	3 P + E	6H
<b>318.12547</b>	125 Amp	3 P + N + E	6H

\* 3H = Refrigerated Container

Fittings 63 Amp and above have Pilot Pin and are IP67 Rated

### IP44 OPTIMA Connector

Code	Rating	Pins	Earth Position
<b>240v BLUE</b>			
<b>313.1643PTR</b>	16 Amp	2 P + E	6H Ins. Perforation
<b>313.1643TR</b>	16 Amp	2 P + E	6H
<b>313.3243</b>	32 Amp	2 P + E	6H
<b>415v RED</b>			
<b>313.1646</b>	16 Amp	3 P + E	6H
<b>313.1647</b>	16 Amp	3 P + N + E	6H
<b>313.3246</b>	32 Amp	3 P + E	6H



### IP44 Angled Connector

Code	Rating	Pins	Earth Position
<b>321.1643</b>	16 Amp	2 P + E	6H

International Industrial Standard IEC60309-CEE17

### Insulation Perforating Terminals - Fast Wiring

Insulation perforation saves up to 60% termination time.

**Code Suffix: P or PTR**



### Screw Terminals - Conventional Wiring

Traditional Screw Terminations also available.

