

Recessed Smart Tilt Downlight Kit
LEDE Economy Select 3K/4K



R773



SPECIFICATIONS	
DIMENSIONS	D103 x H54mm
CUT OUT	Ø 92mm
COLOUR TEMP	Selectable 3000K Warm White or 4000K Natural White
LUMENS	White: 3000K Warm White 800lm 4000K Natural White 850lm Black: 3000K Warm White 700lm 4000K Natural White 750lm
CRI	90
LIFESPAN	55,000 hours (L80 B20)
BEAM ANGLE	90°
TILT ANGLE	25° (Patented IP44 smart tilt gasket)
MATERIAL	Aluminium, ADC12, PBT, PC
IP RATING	IP44
CLEARANCE	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
CLASSIFICATION	IC-F Rated
DRIVER	DX Series Under Insulation Dimmable TRIAC Driver Included (pre-wired) 180mA
APPLICATION	Residential / Commercial Interior
WARRANTY	5 Year Warranty

<850
LUMENS

8
WATTS

AC
240V



UID™ Dimmable Under
Insulation Driver Included

select CCT

AVAILABLE IN	
DESCRIPTION	CODE
Black 3000K/4000K Tilt "Select" Dual Colour	R773 B34V3
White 3000K/4000K Tilt "Select" Dual Colour	R773 W34V3