REDUCERS



Hard nylon reducers with excellent mechanical properties

Metric to Metric

Pg to Metric

| <mark>]</mark> ⊡ mm | Ţ <u>ī</u> ₽ mm | тг С mm | Spa mm | Pack size | Cat No. |
|---------------------------|---------------------------|---------------|-----------|--------------|------------|
| M16 | M12 | 8 | 18 | 50 | R16/12 |
| M20 | M16 | 10 | 24 | 50 | R20/16 |
| M25 | M20 | 12 | 30 | 50 | R25/20 |
| M32 | M25 | 12 | 36 | 50 | R32/25 |
| M40 | M32 | 12 | 43 | 10 | R40/32 |
| M50 | M40 | 12 | 53 | 5 | R50/40 |
| M63 | M50 | 12 | 69 | 5 | R63/50 |

| Thread | [o] mm | <u>тр</u> mm | н С т т т т т т т | J¤ m | Pack size | Cat No. |
|--------|-----------|-----------------|---|------|--------------|------------|
| Pg9 | 15.2 | M12 | 8 | 18 | 25 | RPG09/12 |
| Pg11 | 18.6 | M16 | 10 | 22 | 25 | RPG11/16 |
| Pg13.5 | 20.4 | M16 | 10 | 24 | 25 | RPG13/16 |
| Pg16 | 22.5 | M20 | 10 | 27 | 50 | RPG16/20 |
| Pg21 | 28.3 | M20 | 12 | 36 | 25 | RPG21/20 |
| Pg21 | 28.3 | M25 | 12 | 36 | 25 | RPG21/25 |
| Pg29 | 37.0 | M32 | 12 | 43 | 10 | RPG29/32 |
| Pg36 | 47.0 | M32 | 12 | 53 | 5 | RPG36/32 |
| Pg36 | 47.0 | M40 | 12 | 53 | 5 | RPG36/40 |
| | | | | | | |
| | | | | | | |

TECHNICAL DATA

Material: Nylon

Colour: Black or Grey

Working temp: -40°C to 100°C. Short term 130°C

Chemical resistance: Excellent resistance to oils, petrol, alcohols, seawater, caustic soda, weak acids, alkalis, bases and salts.



A product designed and distributed by

McCABE INDUSTRIES LTD

667C High Street, Lower Hutt 5010, New Zealand Ph: 045289619; Email: info@mccabeindustries.co.nz www.mccabeindustries.co.nz