

## Main

Range	PDL Iconic
Aesthetic name	Iconic
Product or component type	Remote control auxiliary

## Complementary


Device presentation	Insert without cover
Range compatibility	Iconic Wiser Dimmer
[Ue] rated operational voltage	220...240 V AC 50 Hz
Number of FUNCTION keys	1
Local signalling	1 LED (green/red) programmable
Signalling function	Programming indication Light ON when switch is actuated Locator
Number of outputs	1
Control type	Local control: dimming up/down control Local control: on/off switching
Communication network type	Wired ControlLink
Connected auxiliaries	1 Wiser dimmer, cable length 50 m
Provided equipment	User manual
Wiring configuration	With neutral
Connections - terminals	Screw terminal
Number of loop terminals	2
Clamping connection capacity	1.5...2.5 mm <sup>2</sup> solid 1.5...2.5 mm <sup>2</sup> solid stranded
Shape of screw head	Pozidriv No 1 and combi
Tightening torque	0.5 N.m
Material	Terminals: metal Casing: PC (polycarbonate) GF10 FR
Mounting support	Wall
Device mounting	Flush
Fixing mode	Clip-in
Type of installation	Indoor installation
Quantity per set	1 carton

Embedding depth	41 mm
Depth	41 mm
Width	22 mm
Height	22 mm

## Environment

Ambient air temperature for operation	5...40 °C
Ambient air temperature for storage	5...40 °C
IP degree of protection	IP20
Standards	AS/NZS CISPR 15 AS/NZS 60669.2.1

## Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1735 - Schneider Electric declaration of conformity  <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>