



Main

Range	Clipsal Iconic
Product or component type	Push-button dimmer
Device presentation	Mechanism

Complementary

Device mounting	Flush
Range compatibility	PDL Iconic
Actuator	Push-button
Fixing mode	Clip-in
Colour tint	Vivid white
Surface finish	Glossy
Type of packing	Box
Sale per indivisible quantity	1
Ambient air temperature for storage	0...60 °C
Dimmer control	Push type
[Ie] rated operational current	1.2 A
[Ue] rated operational voltage	220...240 V AC 50 Hz
Load type	Incandescent lamp 300 W Medium voltage halogen lamp 300 W Low voltage halogen lamp with iron core transformer 300 W Dimmable fluocompact lamp 200 W Dimmable LED lighting driver 200 W Dimmable fluorescent ballast 200 W
Derating factor	Number of devices 4 with derating Number of devices 5 with derating Number of devices 6 with derating Number of devices 1 without derating Number of devices 2 with derating Number of devices 3 with derating
Function available	Brightness adjustment
Control signal type	ControlLink
Protection type	Short-circuit
Protection type	Current overload Thermal protection internal fuse without reset Short-circuit

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	Thermal overload protection
Operating distance	30 m
Control type	Push-button
Remote control type	Without
Connections - terminals	Screw terminal
Screwdriver shape	Philips Square drive no 1 (SQ1)
Number of terminals	3
Local signalling	LED indicator warm white
Material	PC (UL94 V-2) for top PC MAS056 (UL94 V-2) for bottom
Height	23.5 mm
Width	23.5 mm
Depth	42 mm
Embedding depth	39 mm
Standards	AS/NZS 60669.2.1

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1713 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold