



Main

Range	PDL Iconic
Product or component type	Rotary dimmer
Device presentation	Mechanism

Complementary

Device mounting	Clip with locking bar
Range compatibility	PDL Iconic
Actuator	Rotary
Fixing mode	Clip-in
Colour tint	Vivid white
Surface finish	Glossy
Type of packing	Box
Sale per indivisible quantity	1
Ambient air temperature for storage	0...60 °C
Dimmer control	315° rotary setting
[Ie] rated operational current	1.5 A
[Ue] rated operational voltage	220...240 V AC 50 Hz
Load type	Dimmable LED 350 W (240 V AC) Incandescent 350 W (240 V AC) Low voltage halogen lamp with electronic transformer 350 W (240 V AC) Dimmable fluocompact lamp 150 W (240 V AC) Dimmable fluorescent 150 W (240 V AC)
Derating factor	Number of devices 1 without derating Number of devices 2 with derating Number of devices 3 with derating
Function available	Brightness adjustment
Protection type	Short-circuit
Protection type	Current overload Thermal protection internal fuse without reset Short-circuit Thermal overload protection
Remote control type	Without
Connections - terminals	Flying leads
Material	PC (UL94 V-2) for top

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

PC MAS056 (UL94 V-2) for bottom

Height	22.5 mm
Width	22.5 mm
Depth	39 mm
Embedding depth	37 mm
Standards	AS/NZS 60669.2.1

Environment

Ambient air temperature for operation	0...45 °C
Relative humidity	0...90 %

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1713 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold