

## Product data sheet Characteristics

# PDL356PBSS-VW

# PDL Iconic ControlLink Remote Switch Mechanism Momentary PushButton





Main	
Range	PDL Iconic
Product or component type	Timer
Device presentation	Mechanism

#### Complementary

Device mounting	Flush
Actuator	Push-button
Fixing mode	Clip-in
Colour tint	Vivid white
Surface finish	Matt
Type of packing	Вох
Sale per indivisible quantity	1
Remote control type	Push-button
[Ue] rated operational voltage	240 V AC 50 Hz
Operating distance	30 m
Control signal type	ControlLink
Connections - terminals	Screw terminals
Number of terminals	2
Wiring configuration	2-wire
Screwdriver shape	Square drive no 1 (SQ1) Philips
Material	PC (UL94 V-2): top PC MAS056 (UL94 V-2): bottom
Height	22 mm
Width	22 mm
Depth	40 mm
Embedding depth	38 mm

#### Environment

Ambient air temperature for storage	060 °C
Ambient air temperature for operation	045 °C
Relative humidity	090 %

### Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.9 cm
Package 1 Width	6.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	41 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	13 cm
Package 2 Width	9.6 cm
Package 2 Length	15.2 cm
Package 2 Weight	332 g
Unit Type of Package 3	CAR
Number of Units in Package 3	72
Package 3 Height	34.1 cm
Package 3 Width	26.4 cm
Package 3 Length	33.8 cm
Package 3 Weight	4.456 kg

#### Offer Sustainability

Office Oddital dollity	
Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant E EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
-	