

## Product data sheet Characteristics

# PDL381M20

Main

# PDL Iconic Switch Mechanism, Universal Rocker 250 V 20 A/16 Ax1-Way/2-Way





Main	
Range of product	PDL Iconic
Product or component type	Switch
Device application	Lighting
Device presentation	Mechanism
Provided equipment	Switch
Type of packing	Polybag
Quantity per set	Set of 20
Sale per indivisible quantity	1
Motor M-rating AS3133	M100
Load type	Fluorescent 20 A LEDi lamp 250 W Inductive Light Fluorescent lamp

#### Complementary

Switch function	1/2-way	
Fixing mode	Locking bar	
Surface finish	Matt	
Surface treatment	Untreated	
Rated current	20 A/16 AX at 250 V AC 50 Hz	
Electrical durability	20000 cycles conforming to AS/NZS 60669	
Connections - terminals	4 screw terminals	
Screwdriver shape	Square drive no 1 (SQ1) Philips No 2	
Clamping connection capacity	1.5 mm² for stranded cable(s) 1.5 mm² for flexible cable(s) 1.5 mm² for rigid cable(s)	
Wire stripping length	10 mm	
Material	PC (polycarbonate): housing PA66: housing	
Height	23 mm	
Width	23 mm	
Depth	32 mm	
Net weight	0.02 kg	

#### Environment

Dielectric strength	5000 V
Ambient air temperature for operation	045 °C
Ambient air temperature for storage	060 °C
Relative humidity	1095 %
Product certifications	RCM

### Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.3 cm	
Package 1 Width	2.3 cm	
Package 1 Length	1.8 cm	
Package 1 Weight	18 g	

# Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile