

## Product data sheet

### Characteristics

# PDL381VWP-VW

PDL Iconic Switch, Vertical 1 Gang, 1/2 Way  
10AX, 250V, IP44



### Main

Range of product	PDL Iconic
Product or component type	Switch
Device application	Lighting
Device presentation	Complete switch
Provided equipment	IP44 gridplate and switch Screws Skin
Colour	Vivid white (VW)
Type of packing	Polybag
Quantity per set	Set of 20
Sale per indivisible quantity	1
Motor M-rating AS3133	M80

### Complementary

Device mounting	Flush
Switch function	1/2-way
Number of gangs	1 gang vertical 84 mm
Number of rocker	1
Actuator	Rocker
Fixing mode	By screws
Surface finish	Matt
Surface treatment	Untreated
Rated current	20 A/16 AX at 250 V AC 50 Hz
Electrical durability	20000 cycles conforming to AS/NZS 60669
Connections - terminals	4 screw terminals
Screwdriver shape	Square drive no 1 (SQ1) Philips No 2
Clamping connection capacity	1.5 mm <sup>2</sup> for stranded cable(s) 1.5 mm <sup>2</sup> for flexible cable(s) 1.5 mm <sup>2</sup> for rigid cable(s)
Wire stripping length	10 mm
Material	PC (polycarbonate): skin ABS (acrylonitrile butadiene-styrene): skin PC (polycarbonate): grid plate PP (polypropylene): flaps PC (polycarbonate): housing PA66: housing POM (polyoxymethylene): locking bar TPE (thermoplastic elastomer): switch seal PC (polycarbonate): wall seal TPE (thermoplastic elastomer): wall seal
Height	124 mm
Width	82 mm
Depth	40 mm
Net weight	0.098 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Ambient air temperature for operation	0...45 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	10...95 %
Product certifications	RCM
IP degree of protection	IP44

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.9 cm
Package 1 Width	7.8 cm
Package 1 Length	8 cm
Package 1 Weight	80 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>