

## Product data sheet

### Characteristics

# PDL343USBG

PDL Iconic 3 Gang, USB Charging Station,  
220-240VAC, 3x2.1A



### Main

Range	PDL Iconic
Product or component type	USB charger
[Ue] rated operational voltage	220/240 V AC 50 Hz
Integrated connection type	3 USB 2.0 type A 5 V DC, maximum load current: 2.1 A
Maximum load current with 2 outputs used simultaneously	4.5 A






### Complementary

Device mounting	Flush
Device presentation	Mechanism with fixing frame
Colour tint	Vivid white
Surface finish	Matt Textured
Fixing mode	By screws
Type of packing	Polybag
Sale per indivisible quantity	1
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-5...50 °C
Relative humidity	15...95 %
Protection type	Short time short-circuit protection
Number of terminals	3 screw terminal
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	4 x 2.5 mm <sup>2</sup> for stranded cable(s) 4 x 2.5 mm <sup>2</sup> for flexible cable(s) 4 x 2.5 mm <sup>2</sup> for rigid cable(s)
Wire stripping length	10 mm
Height	71 mm
Width	40 mm
Depth	40 mm
Embedding depth	35 mm

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1 cm
Package 1 Width	1 cm
Package 1 Length	1 cm
Package 1 Weight	1 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#"> REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#"> EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#"> Yes</a>
China RoHS Regulation	<a href="#"> China RoHS Declaration</a>
Environmental Disclosure	<a href="#"> Product Environmental Profile</a>