

## Product data sheet

### Characteristics

# PDL382GM10

## Grid and Mechanism, Vertical, 10AX,250VAC, 2 Gang



### Main

Range of product	Iconic
Range of product	Iconic
Product or component type	Grid plate
Device presentation	Mechanism with fixing frame
Load type	Fluorescent 10 A LEDi lamp 100 W

### Complementary

Device mounting	Flush
Number of gangs	2 gangs
Range compatibility	Iconic
Rated current	10 AX at 250 V AC
Local signalling	Without light indicator

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	7.1 cm
Package 1 Length	11.5 cm
Package 1 Weight	74.0 g

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.