

Product data sheet

Characteristics

PDLWSW202LEGY

Surface Switch Weatherprotected, 2 Gang, 20A, 230/240V



Main

Range of product	WP Series
Product or component type	Switch
Switch function	1-pole 2-way
Control type	Rocker
Material	PC (polycarbonate)
Colour tint	Light grey

Complementary

Surface finish	Gloss
Installation direction	Horizontal
Width	84 mm
Height	84 mm
Depth	72 mm
Rated current	20 A 16 AX
Motor M-rating AS3133	M60
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Number of gangs	2 gangs
Mounting mode	Surface mounted
IP degree of protection	IP56
Product specific application	Suits WE1 or WE1S enclosures
Clamping connection capacity	2 x 2.5 mm ² 4 x 1.5 mm ²
Type of packing	Carton

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	8.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	0.093 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	3456
Package 2 Height	210 cm
Package 2 Width	115 cm
Package 2 Length	115 cm
Package 2 Weight	335952.0 g
Unit Type of Package 3	BB1

Number of Units in Package 3	6
Package 3 Height	8.6 cm
Package 3 Width	12.8 cm
Package 3 Length	17.5 cm
Package 3 Weight	608.3 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile