



P D L

NEW PRODUCT DATA AND APPLICATION SHEET

CATALOGUE

WSO310LE

WSO315LE

DESCRIPTION

Single Socket 10A IP53

Single Socket 15A IP53

BARCODE

9416175232183

9416175232336

DESCRIPTION

Weather Protected Sockets to IP53



WSO310



WSO315

BOX QUANTITY 6

OUTER QUANTITY 72

FEATURES

- Aesthetically superior design
- Standard and new shallow low profile mounting options
- Available in light grey
- Protection rating IP53
- Socket face angled and oriented for ease of use and weather protection
- Safety shuttered sockets for additional safety
- Internal phase wiring between switch and socket
- Large clearly marked terminals, centrally located creating more room for ease of wiring
- Latest technology materials with superior UV protection, impact strength, and additional chemical resistance when compared with polycarbonates
- Channelled red gaskets
- Pad lockable option as standard
- Captivated stainless steel fixing screws, only two screws needed
- Suits WE1 and WE1S enclosures
- Enclosures (bases) supplied separately

Standard Size:

- Base includes 90° mounting options for added flexibility
- Multiple cable entry points for ease of wiring
- Multiple mounting points away from rear entry and conduit entry points for ease of installation

Shallow Low Profile Size:

- Addition mounting options to the standard base for fitting to round conduit boxes
- Single 20mm rear cable entry point, expandable to 32mm



P D L

NEW PRODUCT DATA AND APPLICATION SHEET

- SPECIFICATIONS**
- 230-240V a.c. 50Hz.
 - 10A – WSO310; 15A - WSO315
 - Terminals accommodate 3 x 6mm² , or 4 x 2.5mm²
 - Complies with AS/NZS3100; AS/NZS3112; and AS1939
 - IP53
 - Enclosures (bases) supplied separately

Standard Size:

- Five plain 25mm conduit entry points – single and double options
- Rear 25mm cable entry plug
- Plain and threaded 25-20mm reducers supplied as appropriate
- Standard Dimensions: 84mm x 84mm x 85mm

Shallow Low Profile Size:

- Rear cable entry 20mm, expandable to 32mm
- Shallow Dimensions: 84mm x 84mm x 68mm

- APPLICATIONS**
- IP53 power supply socket outlets for a vast array of applications including, garden lighting, water features, fixed appliances, general purpose outlets, power tools, outdoor plant control, gas water heating (instant and cylinder), small air-conditioning units, generators, caravans, portable building supply, plus many others