

Product data sheet

Characteristics

PDL682WH

Flush Switch, 20A/16AX/M60, 2 Gang, Surface Mounted



Main

Range of product	600 Series
Product or component type	Switch
Control type	Rocker

Complementary




Material	PC (polycarbonate)
Colour tint	White
Surface finish	Gloss
Installation direction	Horizontal Vertical
Length	118 mm
Width	74 mm
Rated current	20 A 16 AX
[Ue] rated operational voltage	250 V
Network type	AC
Motor M-rating AS3133	M60
Number of gangs	2 gangs
Number of poles	1
Mounting mode	Surface mounted
Fixing center	84 mm
Ambient air temperature for operation	-10...40 °C
Cable cross section	2 x 2.5 mm ² 4 x 1.5 mm ²

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.5 cm
Package 1 Width	7.5 cm
Package 1 Length	12 cm
Package 1 Weight	0.083 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	100
Package 2 Height	20 cm
Package 2 Width	31.7 cm
Package 2 Length	62.1 cm

Package 2 Weight	8.3 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	1200
Package 3 Height	110 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	99.6 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile