

Product data sheet Characteristics

PDL56SW116LEGY Switch, 16A, 250V, 1-Pole





| Main | |
|---------------------------|---------------|
| Range of product | 56 Series™ |
| Product or component type | Rotary switch |
| Colour tint | Grey |
| Motor M-rating AS3133 | M120 |
| Quantity per set | Set of 4 |
| Type of packing | Carton |

Complementary

| Number of poles | 1 | |
|--------------------------------|--------------------|--|
| Control type | Rotary | |
| Material | PC (polycarbonate) | |
| Surface finish | Gloss | |
| Installation direction | Vertical | |
| Width | 95 mm | |
| Height | 95 mm | |
| Depth | 62 mm | |
| Rated current | 16 A | |
| [Ue] rated operational voltage | 240 V | |
| Network frequency | 50 Hz | |
| Network number of phases | 1 phase | |
| Number of gangs | 1 gang | |
| Mounting mode | Surface mounted | |
| Fixing center | 84 x 84 mm | |
| Cable cross section | 0.756 mm² | |

Environment

| IP degree of protection | IP66 |
|---------------------------------------|----------|
| Ambient air temperature for operation | -4055 °C |

Packing Units

| Number of Units in Package 1 1 Package 1 Height 8.5 cm | |
|--|--|
| Package 1 Height 8.5 cm | |
| | |
| Package 1 Width 20 cm | |
| Package 1 Length 21 cm | |
| Package 1 Weight 0.991 kg | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|---------------------------------|--|
| REACh Regulation | ☑ REACh Declaration | |
| EU RoHS Directive | Compliant EEEU RoHS Declaration | |
| Mercury free | Yes | |
| RoHS exemption information | ₫Yes | |
| China RoHS Regulation | ☑ China RoHS Declaration | |
| Environmental Disclosure | Product Environmental Profile | |