

## Product data sheet

### Characteristics

# PDLS380FW

Front Wiring Mains Switch, 80A/M200, 440V, 50Hz, 3 Pole



### Main

|                           |                    |
|---------------------------|--------------------|
| Range of product          | S Series           |
| Product or component type | Switch             |
| Material                  | PC (polycarbonate) |
| Colour tint               | White              |
| Surface finish            | Gloss              |

### Complementary

|                                |                    |
|--------------------------------|--------------------|
| Installation direction         | Vertical           |
| Width                          | 52.5 mm            |
| Height                         | 70 mm              |
| Depth                          | 51 mm              |
| Rated current                  | 80 A               |
| [Ue] rated operational voltage | 440 V              |
| Network frequency              | 50 Hz              |
| Motor M-rating AS3133          | M200               |
| Number of poles                | 3                  |
| Mounting mode                  | Surface mounted    |
| IP degree of protection        | IP66               |
| Cable cross section            | 25 mm <sup>2</sup> |
| Quantity per set               | Set of 1           |
| Type of packing                | Carton             |

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 4.5 cm   |
| Package 1 Width              | 6 cm     |
| Package 1 Length             | 7 cm     |
| Package 1 Weight             | 0.175 kg |

### Offer Sustainability

|                   |                     |
|-------------------|---------------------|
| EU RoHS Directive | Under investigation |
|-------------------|---------------------|