

Product data sheet

Characteristics

PDLS380BW

Back Wiring Mains Switch - S series - 80A/ M200, 440V, 50 Hz, 3P



Main

| | |
|---------------------------|--------------------|
| Range of product | S Series |
| Product or component type | Switch |
| Material | PC (polycarbonate) |
| Colour tint | White |
| Surface finish | Gloss |

Complementary

| | |
|--------------------------------|--------------------|
| Installation direction | Vertical |
| Width | 52.5 mm |
| Height | 70 mm |
| Depth | 51 mm |
| Rated current | 80 A |
| [Ue] rated operational voltage | 440 V |
| Network frequency | 50 Hz |
| Motor M-rating AS3133 | M200 |
| Number of poles | 3 |
| Mounting mode | Surface mounted |
| IP degree of protection | IP66 |
| Cable cross section | 25 mm ² |
| Quantity per set | Set of 1 |
| Type of packing | Carton |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5 cm |
| Package 1 Width | 6 cm |
| Package 1 Length | 7 cm |
| Package 1 Weight | 0.17 kg |

Offer Sustainability

| | |
|-------------------|---------------------|
| EU RoHS Directive | Under investigation |
|-------------------|---------------------|