

Product data sheet Characteristics

PDL26BK

Unswitched Cordgrip Lampholder, Lighting, 3A, 250V, 150W



Main

| Mani | |
|---------------------------|------------------------------|
| Range of product | PDL Lighting and Accessories |
| Product or component type | Button module |
| Colour tint | Black |
| Load type | 150 W lamp |
| Quantity per set | Set of 20 |
| Type of packing | Carton |

Complementary

| Material | Thermoplastic | |
|--------------------------------|--------------------------------|--|
| Surface finish | Glossy | |
| [In] rated current | 3 A | |
| [Ue] rated operational voltage | 250 V 50 Hz | |
| Network number of phases | 1 phase | |
| Mounting support | Cord grip Suspended ceiling | |
| Connections - terminals | 4 x 1 mm screw terminal | |

Packing Units

| r doking office | | |
|------------------------------|----------|--|
| Unit Type of Package 1 | PCE | |
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 4.0 cm | |
| Package 1 Width | 4.0 cm | |
| Package 1 Length | 7.0 cm | |
| Package 1 Weight | 0.038 kg | |
| | | |

Offer Sustainability

| One Cadamasing | | |
|-------------------|---------------------|--|
| EU RoHS Directive | Under investigation | |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.