

## Product data sheet

### Characteristics

# PDLS220EM

1-Way Enclosed Main Switch; 20A, 415VAC, 50 Hz, 2P



### Main

Range of product	S Series
Product or component type	Switch
Material	PC (polycarbonate)
Colour tint	White
Surface finish	Gloss

### Complementary

Installation direction	Vertical
Width	82 mm
Height	165 mm
Depth	81 mm
Rated current	20 A
[Ue] rated operational voltage	415 V
Network frequency	50 Hz
Motor M-rating AS3133	M125
Number of poles	2
Mounting mode	Surface mounted
IP degree of protection	IP66
Cable cross section	16 mm <sup>2</sup>
Quantity per set	Set of 1
Type of packing	Carton

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.9 cm
Package 1 Width	8.3 cm
Package 1 Length	16.7 cm
Package 1 Weight	430 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	18.8 cm
Package 2 Width	17.7 cm
Package 2 Length	41.7 cm
Package 2 Weight	4300.0 g
Unit Type of Package 3	PAL
Number of Units in Package 3	480
Package 3 Height	112.8 cm
Package 3 Width	70.8 cm

Package 3 Length	83.4 cm
Package 3 Weight	206400.0 g

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------