

## Product data sheet Characteristics

# PDL681M20BK

Switch Module, 2 way, 20A/16AX/M60, 250VAC 50 Hz, 1 Pole





#### Main

IVIAIII	
Range of product	600 Series
Product or component type	Switch
Control type	Rocker

#### Complementary

Material	PC (polycarbonate)
Colour tint	Black
Surface finish	Gloss
Installation direction	Vertical Horizontal
Length	23 mm
Width	23 mm
Depth	26 mm
Rated current	16 AX 20 A
[Ue] rated operational voltage	250 V
Network type	AC
Motor M-rating AS3133	M60
Network number of phases	1 phase
Number of gangs	1 gang
Number of poles	1
Mounting mode	Front
Ambient air temperature for operation	-1040 °C
Cable cross section	2 x 2.5 mm <sup>2</sup> 4 x 1.5 mm <sup>2</sup>

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3 cm	
Package 1 Width	2.5 cm	
Package 1 Length	2.5 cm	
Package 1 Weight	14.035 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	20	
Package 2 Height	4.4 cm	
Package 2 Width	13.65 cm	

Package 2 Length	13.65 cm
Package 2 Weight	0.338 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	400
Package 3 Height	24 cm
Package 3 Width	29 cm
Package 3 Length	33 cm
Package 3 Weight	7.13 kg

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	<sup>™</sup> REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	☑ Product Environmental Profile	