

## Product data sheet

### Characteristics

# ACTPP6U24NSS

## Category6, UTP 24-Port Non-Shutter Patch Panel, Loaded



### Main

Range of product	Actassi
Product or component type	Patch panel
Device presentation	Loaded
Provided equipment	With RJ45 connectors

### Complementary

[In] rated current	1.5 A
Number of port	24 port of UTP
Product compatibility	Standard 19" cabinet/rack
Communication network category	6
Contact resistance	1 mOhm
Insulation resistance	>= 200 MOhm
Minimum number of matings	1000 cycles
Number of rack unit	1U
Type of connector	S-110 keystone



### Environment

Ambient air temperature for operation	-40...70 °C
Standards	ANSI/TIA/EIA-568-B ISO/IEC 11801 Ed.2, 2002

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	15 cm
Package 1 Length	46.5 cm
Package 1 Weight	1 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes

---

China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

---

### Contractual warranty

---

Warranty	18 months
----------	-----------

---