



Main

Range	Resi9
Product or component type	Residual current breaker with overcurrent protection (RCBO)
Poles description	1P + N
Number of protected poles	1
[In] rated current	32 A at 30 °C conforming to AS/NZS 61009.1
Network type	AC
Curve code	C
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type A
Breaking capacity	6000 A Icn at 230 V AC 50/60 Hz
Quality labels	RCM

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	230 V AC 50/60 Hz
Limitation class	3
[Ui] rated insulation voltage	440 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	4 kV
Comb busbar and distribution block compatibility	YES
9 mm pitches	2
Height	93 mm
Width	18 mm
Depth	73 mm
Net weight	136 g
Grid distance	45 mm

Connections - terminals	Tunnel type terminal (top) - 1...16 mm ² - rigid Tunnel type terminal (top) - 1...10 mm ² - flexible Tunnel type terminal (bottom) - 1...10 mm ² - rigid Tunnel type terminal (bottom) - 1...6 mm ² - flexible
Temperature derating table	-25 °C (38 A) -20 °C (37.5 A) -15 °C (37 A) -10 °C (36.4 A) -5 °C (35.9 A) 0 °C (35.4 A) 5 °C (34.8 A) 10 °C (34.3 A) 15 °C (33.7 A) 20 °C (33.2 A) 25 °C (32.6 A) 30 °C (32 A) 35 °C (31.4 A) 40 °C (30.8 A) 45 °C (30.2 A) 50 °C (29.5 A) 55 °C (28.9 A) 60 °C (28.2 A) 65 °C (27.5 A) 70 °C (26.8 A)

Environment

Standards	IEC 61009-2-2 EN/IEC 61009-1 AS/NZS 61009.1
IP degree of protection	IP20
Pollution degree	2
Overvoltage category	III
Ambient air temperature for operation	-25...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.58 cm
Package 1 Width	1.8 cm
Package 1 Length	9.6 cm
Package 1 Weight	0.15 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information