



Main

Range	Resi9
Product or component type	Enclosure
Device application	Distribution
Number of 18 mm modules per row	15
Provided equipment	Earthing bar Neutral bar Circuit identification label Blanking plate
Colour	White electric (RAL 9003)
Door type	Plain door - right and left

Complementary

Enclosure mounting	Flush
Number of horizontal rows	1
[Ue] rated operational voltage	230/400 V AC
[In] rated current	100 A
[Ui] rated insulation voltage	500 V
Number of ways	15 ways
Cable entry	Knock-out cable entries
Type of rail	DIN
Enclosure material	Housing: plastic
Width	376 mm
Height	258 mm
Depth	104 mm

Environment

Standards	AS/NZS 61439-3 AS/NZS 3000
Fire resistance	650 °C
IP degree of protection	IP40
IK degree of protection	IK05

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.7 cm
Package 1 Width	27 cm
Package 1 Length	38 cm
Package 1 Weight	2.25 kg

Offer Sustainability

REACH Regulation	🔗 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) 🔗 EU RoHS Declaration
China RoHS Regulation	🔗 China RoHS Declaration
Environmental Disclosure	🔗 Product Environmental Profile
Circularity Profile	🔗 End Of Life Information