Product data sheet Characteristics

PDL681WH

2-Way Flush Switch; 20A/16AX/M60, 1-Gang, 1P, White



n	νл		п	n
-11	VΙ	$\boldsymbol{\neg}$		

TTTOMTT		
Range of product	600 Series	
Product or component type	Switch	
Control type	Rocker	

Complementary

Material	PC (polycarbonate)	produ
Colour tint	White	l nese
Surface finish	Gloss	of th
Installation direction	Vertical	reliability
	Horizontal	
Length	74 mm	lity or
Width	118 mm	suitability
Rated current	16 AX	
	20 A	mini
[Ue] rated operational voltage	250 V	determining
Network type	AC	ed for
Motor M-rating AS3133	M60	Sn
Number of gangs	1 gang	t to be
Number of poles	1	is not
Mounting mode	Surface mounted	r and
Fixing center	84 mm	rte fo
Ambient air temperature for operation	-1040 °C	substitute
Cable cross section	1.5 mm² 4	a
	2.5 mm² 2	ed as
		-ĕ

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1250 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product end of life instructions	Need no specific recycling operations	