

Product data sheet Characteristics

16940

auxiliary contact - 1 NC + 1 OC - 380..415 V - 6 A - for RCCB



Main Range of product Multi 9 Product or component OC contact type Device short name OFSP 1 C/O Signal contacts 1 NC composition [In] rated current 3 A: 380...415 V AC - 50/60 Hz 6 A: 220...240 V AC - 50/60 Hz 1 A: 130 V DC 1.5 A: 60 V DC 2 A: 48 V DC 6 A: 24 V DC

Complementary

Mounting mode	Fixed	
Mounting support	DIN rail	
Connections - terminals	Tunnel type terminal2 cable(s) 11.5 mm² - flexible Tunnel type terminal2 cable(s) 11.5 mm² - rigid	
Tightening torque	0.8 N.m	

Environment

2.1711.0111.011		
Standards	EN/IEC 60947-5-1	
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1	
Pollution degree	3 conforming to EN/IEC 60947-5-1	
Ambient air temperature for operation	-2550 °C	
Ambient air temperature for storage	-4085 °C	;

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	52 g	
Package 1 Height	2.7 cm	
Package 1 width	8.1 cm	
Package 1 Length	9.5 cm	
Unit Type of Package 2	S03	
Number of Units in Package 2	45	
Package 2 Weight	2.746 kg	
Package 2 Height	30 cm	
Package 2 width	30 cm	
Package 2 Length	40 cm	

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

	·
Warranty	18 months