

Product data sheet

Characteristics

A9A15096

contact OC - for iSW - 3A - 415V



Main

Range of product	Acti 9
Device short name	IOF
Product or component type	OC contact
Signal contacts composition	1 C/O

Complementary

[Ie] rated operational current	3 A at 415 V AC 6 A at 250 V AC
Mounting mode	Fixed
Mounting support	35 mm DIN rail
9 mm pitches	2
Height	77 mm
Width	18 mm
Depth	75 mm
Colour	White
Range compatibility	Acti 9 iSW
Auxiliary connection terminal	Screw terminal 10 mm ²

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	62 g
Package 1 Height	2.5 cm
Package 1 width	7.5 cm
Package 1 Length	8.3 cm
Unit Type of Package 2	S03
Number of Units in Package 2	108
Package 2 Weight	7.91 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	9
Package 3 Weight	617 g
Package 3 Height	8.5 cm
Package 3 width	9.3 cm
Package 3 Length	22.1 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------