

## Product data sheet

### Characteristics

# A9A15219

modular safety transformer iTR - 230 V 50..60 Hz - output 12..24 V - 25 VA



### Main

Transformer type	Safety transformer
Range	Acti 9
Range of product	Acti 9
Product name	Acti 9 iTR
Product or component type	Transformer
Device short name	ITR

### Complementary

[Ue] rated operational voltage	230 V AC 50/60 Hz
Output voltage	12/24 V: +/-5 % on load 14/28 V: off load
Output short-circuit protection	Built-in
Rated power in VA	25 VA
Temperature derating table	25 VA 35 °C 23.75 VA 40 °C 20 VA 50 °C 15 VA 55 °C 11.25 VA 60 °C
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	10
Height	89 mm
Width	90 mm
Depth	60 mm
Colour	White
Auxiliary connection terminal	Tunnel type terminals 4 mm <sup>2</sup>

### Environment

Standards	EN 61558-2-6 IEC 61558-2-6 EN 60742
Product certifications	NF
Overvoltage category	Class II with terminal shields in option
Ambient air temperature for operation	-20...55 °C
Ambient air temperature for storage	-25...80 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.144 kg
Package 1 Height	8 cm
Package 1 width	10 cm

Package 1 Length	10 cm
Unit Type of Package 2	S02
Number of Units in Package 2	8
Package 2 Weight	9.419 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------