

Product data sheet

Characteristics

A9N15646

Acti9 - fuse-disconnector STI - 1 pole + N - 25 A - for fuse 10.3 x 38 mm



Main

| | |
|---------------------------|-------------------|
| Range | Acti 9 |
| Product name | Acti 9 STI |
| Product or component type | Fuse-disconnector |
| Device short name | STI |
| Poles description | 1P + N |

Complementary

| | |
|--------------------------------|---|
| [In] rated current | 2 A 4 A 6 A 10 A 16 A 20 A 25 A |
| Fuse curve | AM GG |
| Fuse size | 10.3 x 38 mm |
| [Ue] rated operational voltage | 500 V AC |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| 9 mm pitches | 2 |
| Height | 81 mm |
| Width | 18 mm |
| Depth | 75 mm |
| Colour | White |
| Connections - terminals | Screw clamp terminals1 cable(s) 0.75...10 mm ² rigid Screw clamp terminals1 cable(s) 0.5...6 mm ² flexible Screw clamp terminals2 cable(s) 0.75...4 mm ² rigid Screw clamp terminals2 cable(s) 0.5...6 mm ² flexible |
| Wire stripping length | 12 mm |
| Tightening torque | 2 N.m |

Environment

| | |
|---------------------------------------|---------------------------------|
| Standards | IEC 60269-1/2 IEC EN 60947-3 |
| IP degree of protection | IP20 |
| Pollution degree | 3 |
| Ambient air temperature for operation | -20...60 °C |
| Ambient air temperature for storage | -40...80 °C |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 73 g |
| Package 1 Height | 1.8 cm |
| Package 1 width | 7.5 cm |
| Package 1 Length | 8.4 cm |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 12 |
| Package 2 Weight | 927 g |
| Package 2 Height | 2.73 cm |
| Package 2 width | 30 cm |
| Package 2 Length | 20 cm |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 144 |
| Package 3 Weight | 11.661 kg |
| Package 3 Height | 30 cm |
| Package 3 width | 30 cm |
| Package 3 Length | 40 cm |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free product |