## A9N15658

Acti9 - fuse-disconnector STI - 3 poles + N - 25 A - for fuse 10.3 x 38 mm





# Main Range Acti 9 Product name Acti 9 STI Product or component Fuse-disconnector

type

Device short name STI

Poles description 3P + N

Complementary

| Complementary                  |  |  |
|--------------------------------|--|--|
| [ln] rated current             | 2 A  |  |
|                                | 4 A  |  |
|                                | 6 A  |  |
|                                | 10 A   |  |
|                                | 16 A   |  |
|                                | 20 A   |  |
|                                | 25 A   |  |
| Fuse curve                     | AM   |  |
|                                | GG   |  |
| Fuse size                      | 10.3 x 38 mm   |  |
| [Ue] rated operational voltage | 500 V AC   |  |
| [Ui] rated insulation voltage  | 500 V AC 50/60 Hz  |  |
| Mounting mode                  | Clip-on  |  |
| Mounting support               | DIN rail   |  |
| 9 mm pitches                   | 6  |  |
| Height                         | 81 mm  |  |
| Width                          | 54 mm  |  |
| Depth                          | 75 mm  |  |
| Colour                         | White  |  |
| Connections - terminals        | Screw clamp terminals1 cable(s) 0.7510 mm² rigid Screw clamp terminals1 cable(s) 0.56 mm² flexible Screw clamp terminals2 cable(s) 0.754 mm² rigid Screw clamp terminals2 cable(s) 0.56 mm² flexible |  |
| Wire stripping length          | 12 mm  |  |
| Tightening torque              | 2 N.m  |  |

#### Environment

| Littlioninent                   |  |  |
|---------------------------------|--|--|
| IEC 60269-1/2<br>IEC EN 60947-3 |  |  |
| IP20                            |  |  |
| 3                               |  |  |
| -2060 °C                        |  |  |
| -4080 °C                        |  |  |
|                                 |  |  |

### Packing Units

| •                            |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 182 g    |
| Package 1 Height             | 5.4 cm   |
| Package 1 width              | 7.5 cm   |
| Package 1 Length             | 8.6 cm   |
| Unit Type of Package 2       | BB1      |
| Number of Units in Package 2 | 4        |
| Package 2 Weight             | 785 g    |
| Package 2 Height             | 3.9 cm   |
| Package 2 width              | 30 cm    |
| Package 2 Length             | 20 cm    |
| Unit Type of Package 3       | S03      |
| Number of Units in Package 3 | 48       |
| Package 3 Weight             | 9.961 kg |
| Package 3 Height             | 30 cm    |
| Package 3 width              | 30 cm    |
| Package 3 Length             | 40 cm    |
|                              |          |

#### Offer Sustainability

| Custoinable offer status    | Cross Promises and dust   |
|-----------------------------|---|
| Sustainable offer status    | Green Premium product   |
| REACh Regulation            | REACh Declaration   |
| REACh free of SVHC          | Yes   |
| EU RoHS Directive           | Compliant E EU RoHS Declaration   |
| Toxic heavy metal free      | Yes   |
| Mercury free                | Yes   |
| RoHS exemption information  | ₫Yes  |
| China RoHS Regulation       | ☑ China RoHS Declaration  |
| Environmental Disclosure    | Product Environmental Profile   |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free product  |