# Product data sheet Characteristics

## NSYCRN43200P

Spacial CRN plain door with mount.plate. H400xW300xD200 IP66 IK10 RAL7035...





#### Main Range Spacial Product name Spacial CRN Application Multi-purpose Category Compact enclosure Enclosure nominal 400 mm height 300 mm Enclosure nominal width Enclosure nominal 200 mm depth Installation accessory Wall-mounting type Device composition 1 body 1 cable gland plate 1 door with lock 1 mounting plate Door type Plain Mounting plate Plain

### Complementary

Body type	Sides made from a single folded section  Back welded with double profile forming a protected sealed area
Number of doors	Front face: 1 door(s)
Door opening side	Reversible (120 °)
Lock type	3 mm double-bar lock
Type of gland plate	Standard
Accessibility for operation	Front
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element
Material	Enclosure: steel Mounting plate: galvanised steel
Surface finish	Enclosure: epoxy-polyester powder
Colour	Enclosure: grey (RAL 7035)
Standards	IEC 62208
Product certifications	CUL UL DNV-GL
Product weight	6.946 kg

description

#### Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	7.104 kg	
Package 1 Height	22 cm	
Package 1 width	31 cm	
Package 1 Length	42 cm	

## Offer Sustainability

Green Premium product
REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
₫Yes
China RoHS Declaration
☐ Product Environmental Profile

## Contractual warranty

Warranty 18 month	
-------------------	--