NSYPLA10103G

Floor standing enclosure polyester vers.PLA completely sealed 1000x1000x320 IP65





Main Range Thalassa Product name Thalassa PLA Enclosure type Multi-purpose Product or component Suitable enclosure type PLA Version 1000 mm Nominal height Nominal width 1000 mm Nominal depth 320 mm **Enclosure mounting** Floor-standing Device composition 1 top part 1 bottom part

2 side part 1 rear panel 2 door

Complementary

Body type	Sealed top and bottom part assembled with side parts	
Door type	Plain front	
Number of doors	2 door(s)	
Door opening side	Right and left (120 °)	
Lock type	4 points lock, 5 mm double-bar	
Accessibility for operation	Front Rear	
Removable parts	Door by hinges Rear panel by fixing element	
Material	Polyester reinforced with fibreglass	
Colour	Grey (RAL 7035)	
Standards	IEC 62208 UL 508 A	
NEMA degree of protection	NEMA 12 NEMA 1 NEMA 13 NEMA 2	
Product certifications	Veritas DNV Marine UL/cUL listed	
Electrical insulation class	Class II	

Environment

IP degree of protection	IP65 conforming to IEC 60529 (completely sealed)
IK degree of protection	IK10 conforming to IEC 62262 (plain door)
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for storage	-3590 °C

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	41 kg	
Package 1 Height	105 cm	
Package 1 width	38.5 cm	
Package 1 Length	103 cm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile