

Product data sheet

Characteristics

PDL354RDMLLED-VW

PDL Iconic, dimmer, 300M, LED, rotary, 350 W, Vivid White



Main

Range	PDL Iconic
Product or component type	Dimmer
Device presentation	Mechanism
Colour tint	Vivid white (VW)
Type of packing	Box
Load type	Dimmable LED - 350 W - 240 V AC Incandescent - 350 W - 240 V AC Low voltage halogen lamp with electronic transformer - 350 W - 240 V AC Dimmable fluocompact lamp - 150 W - 240 V AC Dimmable fluorescent - 150 W - 240 V AC

Complementary

Range compatibility	PDL Iconic
Control type	Rotary knob
Fixing mode	Clip-in
Surface finish	Glossy
Ambient air temperature for storage	0...60 °C
Dimmer control	315° rotary setting
[Ie] rated operational current	1.5 A
[Ue] rated operational voltage	220...240 V AC 50 Hz 1 W
Function available	Brightness adjustment
Protection type	Short-circuit
Ambient air temperature for operation	0...45 °C
Relative humidity	0...90 %
Connections - terminals	Flying leads
Material	PC (UL94 V-2): top PC MAS056 (UL94 V-2): bottom
Height	22.5 mm
Width	22.5 mm
Depth	39 mm
Embedding depth	37 mm

Environment

Derating factor	1 deviceswithout derating 2 deviceswith derating factor 3 deviceswith derating factor
Standards	AS/NZS 60669.2.1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	53 g
Package 1 Height	3.9 cm
Package 1 width	6.7 cm

Package 1 Length	8.7 cm
Unit Type of Package 2	PAL
Number of Units in Package 2	1296
Package 2 Weight	68.688 kg
Package 2 Height	150 cm
Package 2 width	114 cm
Package 2 Length	114 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	6
Package 3 Weight	404 g
Package 3 Height	13 cm
Package 3 width	9.6 cm
Package 3 Length	15.2 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information