

## Product data sheet

### Characteristics

# PDL380M20DP

Iconic - Double Pole switch mechanism 20AX  
250V



### Main

|                               |  |
|-------------------------------|--|
| Range of product              | PDL Iconic                             |
| Product or component type     | Switch                                 |
| Device application            | Appliances<br>Lighting                 |
| Device presentation           | Mechanism                              |
| Provided equipment            | Switch                                 |
| Type of packing               | Polybag                                |
| Quantity per set              | Set of 20                              |
| Sale per indivisible quantity | 1                                      |
| Motor M-rating AS3133         | M100                                   |
| Load type                     | Inductive<br>Light<br>Fluorescent lamp |

### Complementary

|                              |  |
|------------------------------|--|
| Switch function              | 2-pole 1-way   |
| Fixing mode                  | Locking bar  |
| Rated current                | 20 AX at 250 V AC 50 Hz  |
| Electrical durability        | 20000 cycles conforming to AS/NZS 60669  |
| Connections - terminals      | 4 screw terminals  |
| Screwdriver shape            | Philips No 2<br>Square drive no 1 (SQ1)  |
| Clamping connection capacity | 1.5 mm <sup>2</sup> for stranded cable(s)<br>1.5 mm <sup>2</sup> for flexible cable(s)<br>1.5 mm <sup>2</sup> for rigid cable(s) |
| Wire stripping length        | 10 mm  |
| Material                     | PC (polycarbonate): housing<br>PA66: housing   |
| Height                       | 23 mm  |
| Width                        | 23 mm  |
| Depth                        | 32 mm  |
| Product weight               | 0.02 kg  |

### Environment

|                                       |           |
|---------------------------------------|-----------|
| Dielectric strength                   | 5000 V    |
| Ambient air temperature for operation | 0...45 °C |
| Ambient air temperature for storage   | 0...60 °C |
| Relative humidity                     | 10...95 % |
| Product certifications                | RCM       |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

|                              |       |
|------------------------------|-------|
| Unit Type of Package 1       | PCE   |
| Number of Units in Package 1 | 1     |
| Package 1 Weight             | 31 g  |
| Package 1 Height             | 23 mm |
| Package 1 width              | 28 mm |
| Package 1 Length             | 31 mm |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |