

Product data sheet Characteristics

PDL392X-VW

PDL Iconic, switched socket, 3 switch & 2 socket, vert, 10 A, Vivid White





| Main | |
|----------------------------|---------------------|
| Range | PDL Iconic |
| Product or component type | Switched socket |
| Device presentation | Complete product |
| Outlet poles configuration | 2P + E with shutter |

Complementary

| Device mounting | Flush |
|--------------------------------|---|
| Number of power socket outlets | 2 |
| Number of rocker | 3 |
| Range compatibility | socket-outlet |
| Outlet standard description | With earthing contact |
| Outlet standard | Australian/New Zealand |
| Ground lug position | Straight 180° position |
| Fixing mode | By screw |
| Installation direction | Vertical |
| Colour | Vivid white (VW) |
| Surface finish | Matt |
| Type of packing | Polybag |
| Quantity per set | Set of 10 |
| Sale per indivisible quantity | 1 |
| Electrical durability | 12000 cycles |
| Screwdriver shape | Philips No 2 Square drive no 1 (SQ1) |
| Clamping connection capacity | 1 x 2.54 x 2.5 mm² for stranded cable(s) 1 x 2.54 x 2.5 mm² for flexible cable(s) 1 x 2.54 x 2.5 mm² for rigid cable(s) |
| Wire stripping length | 16 mm |
| Material | PC (polycarbonate): skin ABS (acrylonitrile butadiene-styrene): skin PC (polycarbonate): fixing frame PP (polypropylene): flaps POM (polyoxymethylene): shutter PC (polycarbonate): switch PA66: switch POM (polyoxymethylene): locking bar |
| Height | 120 mm |
| Width | 78 mm |
| Depth | 35 mm |
| Product weight | 0.092 kg |

Environment

| Ambient air temperature for storage | 060 °C | |
|---------------------------------------|--|--|
| Ambient air temperature for operation | 045 °C | |
| Relative humidity | 1095 % | |
| Standards | AS/NZS 3133 AS/NZS 60669.1 AS/NZS 3112 | |
| Product certifications | RCM | |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|-------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Weight | 92 g | |
| Package 1 Height | 35 mm | |
| Package 1 width | 78 mm | |
| Package 1 Length | 92 mm | |
| | | |

Offer Sustainability

| Onor Castamasinty | | |
|----------------------------|---------------------------------|--|
| Sustainable offer status | Green Premium product | |
| REACh Regulation | [™] REACh Declaration | |
| REACh free of SVHC | Yes | |
| EU RoHS Directive | Compliant E EU RoHS Declaration | |
| Toxic heavy metal free | Yes | |
| Mercury free | Yes | |
| RoHS exemption information | ₫Yes | |
| China RoHS Regulation | ☑ China RoHS Declaration | |
| Environmental Disclosure | Product Environmental Profile | |
| | | |