

Product data sheet Characteristics

PDL395X-VW

PDL Iconic, switched socket, 3 switch & 2 socket, horiz, 10 A, Vivid White





Main	
Range	PDL Iconic
Product or component type	Switched socket
Device presentation	Complete product
Outlet poles configuration	2P + E with shutter

Complementary

Device mounting	Flush
Number of power socket outlets	2
Number of rocker	3
Range compatibility	socket-outlet
Outlet standard description	With earthing contact
Outlet standard	Australian/New Zealand
Ground lug position	Straight 180° position
Fixing mode	By screw
Installation direction	Horizontal
Colour	Vivid white (VW)
Surface finish	Matt
Type of packing	Polybag
Quantity per set	Set of 10
Sale per indivisible quantity	1
Electrical durability	12000 cycles
Screwdriver shape	Square drive no 1 (SQ1) Philips No 2
Clamping connection capacity	1 x 2.54 x 2.5 mm² for stranded cable(s) 1 x 2.54 x 2.5 mm² for flexible cable(s) 1 x 2.54 x 2.5 mm² for rigid cable(s)
Wire stripping length	16 mm
Material	PC (polycarbonate): skin ABS (acrylonitrile butadiene-styrene): skin PC (polycarbonate): fixing frame PP (polypropylene): flaps POM (polyoxymethylene): shutter PC (polycarbonate): switch PA66: switch POM (polyoxymethylene): locking bar
Height	78 mm
Width	120 mm
Depth	37 mm
Product weight	0.092 kg

Environment

Ambient air temperature for storage	060 °C
Ambient air temperature for operation	045 °C
Relative humidity	1095 %
Standards	AS/NZS 3112 AS/NZS 3133
	AS/NZS 60669.1

Packing Units

Package 1 Weight	92.000 g	
Package 1 Height	35.000 mm	
Package 1 width	78.000 mm	
Package 1 Length	92.000 mm	

Offer Sustainability

Green Premium product	
☑ REACh Declaration	
Yes	
Compliant	
Yes	
Yes	
₫Yes	
☑ China RoHS Declaration	
Product Environmental Profile	
	FEACh Declaration Yes Compliant EU RoHS Declaration Yes Yes Yes China RoHS Declaration