

Product data sheet

Characteristics

PDL681M20BK

Switch 600 Series Mechanism - Single-pole - 1-gang - 250 V - 20 A / 16 AX - Black



Main

| | |
|---------------------------|------------|
| Range of product | 600 Series |
| Product or component type | Switch |
| Control type | Rocker |

Complementary

| | |
|---------------------------------------|--|
| Material | PC (polycarbonate) |
| Colour tint | Black |
| Surface finish | Gloss |
| Installation direction | Vertical Horizontal |
| Length | 23 mm |
| Width | 23 mm |
| Depth | 26 mm |
| Rated current | 16 AX 20 A |
| [Ue] rated operational voltage | 250 V |
| Network type | AC |
| Motor M-rating AS3133 | M60 |
| Network number of phases | 1 phase |
| Number of gangs | 1 gang |
| Number of poles | 1 |
| Mounting mode | Front |
| Ambient air temperature for operation | -10...40 °C |
| Cable cross section | 2 x 2.5 mm ² 4 x 1.5 mm ² |

Packing Units

| | |
|------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 13.3 g |
| Package 1 Height | 30 mm |
| Package 1 width | 25 mm |
| Package 1 Length | 25 mm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |