Product data sheet
Characteristics

PDL695USBWH
Socket Outlet 600 Series - Twin switched - Assembled - Single USB charger - Horizontal - 240 V - 1.2A - White

Green Premium™ Product

Main

Range of product	600 Series
Product or component type	Switched socket

Complementary

Control type	Rocker
Material	PC (polycarbonate)
Colour tint	White
Surface finish	Glossy
Installation direction	Horizontal
Width	118 mm
Height	74 mm
Dimension type	External
[Ue] rated operational voltage	230...240 V 50 Hz 5 V
Device mounting	Surface
Number of gangs	2 gangs
[Ie] rated operational current	1.2 A
Fixing center	84 mm
Ambient air temperature for operation	-10…40 °C
Cable cross section	3 x 2.5 mm²
Cut-out dimensions	50 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.133 kg
Package 1 Height	50 mm
Package 1 width	50 mm
Package 1 Length	119 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Life Is On | Schneider Electric