

## Product data sheet

### Characteristics

# RGZE1S35M

Harmony, Socket with clamp, for RXG1 relays, 10 A, screw connectors, separate contact



### Main

Range of product	Harmony Electromechanical Relays
Product or component type	Socket
Contact terminal arrangement	Separate

### Complementary

Product compatibility	Plug-in relay RXG with 1 C/O contact
[Ui] rated insulation voltage	250 V
[Uimp] rated impulse withstand voltage	6 kV between coil and contact with reinforced insulation 4 kV between contacts with basic insulation 4 kV between terminals and DIN rail with basic insulation
[In] rated current	10 A
[Ue] rated operational voltage	250 V conforming to IEC 300 V conforming to UL
Dielectric strength	5 kV between coil and contact with reinforced insulation 2.5 kV between contacts with basic insulation 3 kV between terminals and DIN rail with basic insulation
Connections - terminals	Screw terminals, 1 x 0.25...1 x 2.5 mm <sup>2</sup> (AWG 22...AWG 14) flexible with cable end Screw terminals, 2 x 0.25...2 x 1 mm <sup>2</sup> (AWG 22...AWG 17) flexible with cable end Screw terminals, 2 x 0.5...2 x 1.5 mm <sup>2</sup> (AWG 20...AWG 16) solid without cable end Screw terminals, 1 x 0.5...1 x 2.5 mm <sup>2</sup> (AWG 20...AWG 14) solid without cable end
Screw type	M3

### Environment

Ambient air temperature for storage	-40...85 °C
Ambient air temperature for operation	-40...70 °C
Relative humidity	10...85 %
Standards	UL 508 CSA C22.2 No 14 IEC 61984
Product certifications	CE EAC UL CSA DNV-GL
IP degree of protection	IP20
Overvoltage category	III
Pollution degree	3


## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	32.1 g
Package 1 Height	62.5 mm
Package 1 width	17 mm
Package 1 Length	81 mm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	365.9 g
Package 2 Height	7.8 cm
Package 2 width	8.4 cm
Package 2 Length	16.3 cm
Unit Type of Package 3	S03
Number of Units in Package 3	180
Package 3 Weight	16.3 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

Dimensions



(1) Maintaining clamp

## Wiring Diagram

