

Product data sheet

Characteristics

VDIG111241F

Actassi 19-C Patch Panel Sliding Evo 19" 1U 24pt S-OneDPM FTP/STP Empty



Main

Range of product	Actassi
Product or component type	Empty sliding 19" data panel
Device presentation	Empty
Provided equipment	4 label holders 2 quick fix 19" mountings 1 connector release tool 1 rear cable organizer
Colour	Dark grey (RAL 7016)
Additional information	Automatic grounding

Complementary

Variant	Evolution
Number of port	24 port of FTP/STP
Communication network category	5e 6 6A
Number of rack unit	1U
Type of connector	S-One DPM
Material	DC01 metal sheet 1.2 mm PA6 plastic part PA66 GF20 plastic part
Width	490 mm
Depth	230 mm
Height	45 mm
Product weight	2.7 kg

Environment

Ambient air temperature for operation	-10...55 °C
Standards	IEC 60297 NF C 20-150

Packing Units

Package 1 Weight	2.500 kg
Package 1 Height	0.500 dm
Package 1 width	3.200 dm
Package 1 Length	5.700 dm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------