

Product data sheet Characteristics

XZCC12FCM50B

Female, M12, 5 pin, elbowed connector, cable gland Pg 7



Main Range of product Telemecanique Cabling components Accessory / separate Cabling accessories part category Accessory / separate Connector part type Electrical connection Elbowed female connector M12, 5 pins Collar material Metal Status LED Without Cable connection Screw terminal / wire size <0.75 mm² / clamping capacity 3...6 mm

Complementary

Cable gland type	Pg 7	
Cable connector fixing	Screw-on	
[Ue] rated operational voltage	30 V AC 36 V DC	
[In] rated current	3 A	
Enclosure material	Plastic	
Minimum insulating resistance	1000 GΩ	
Contact resistance	8000 μOhm	
Product weight	0.02 kg	

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-4085 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	29 g
Package 1 Height	2 cm
Package 1 width	11.5 cm
Package 1 Length	14 cm
Unit Type of Package 2	S01
Number of Units in Package 2	50
Package 2 Weight	1.636 kg
Package 2 Height	15 cm
Package 2 width	15 cm
Package 2 Length	40 cm

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes


Contractual warranty

· · · · · · · · · · · · · · · · · · ·		
Warranty	18 months	

Product data sheet Dimensions Drawings

XZCC12FCM50B

Dimensions



(1) Cable gland : no. 7 plastic (Pg 7)

Product data sheet Connections and Schema

XZCC12FCM50B

Connections and Schemes

