

Product data sheet

Characteristics

ZCKE09

Limit switch head, Limit switches XC Standard, ZCKE, w/o lever stay put left and right actuation



Main

| | |
|----------------------------|--|
| Range of product | Telemecanique Limit switches XC Standard |
| Series name | Standard format |
| Product or component type | Limit switch head |
| Device short name | ZCKE |
| Head type | Rotary head |
| Product compatibility | XCKJ |
| Associated lever | ZCKY71 ZCKY61 |
| Associated body | ZCKJD39 ZCKJ2H7 ZCKJ21H29 ZCKJ9H29 ZCKJ1 ZCKJ21 ZCKJ1H29 ZCKJ2 ZCKJD31H7 ZCKJ11H29 ZCKJ11H7 ZCKJ9H7 ZCKJ2H29 ZCKJD39H7 ZCKJ9 ZCKJ1H7 ZCKJD39H29 ZCKJD31H29 ZCKJ11 ZCKJ21H7 ZCKJD31 |
| Movement of operating head | Rotary |
| Type of operator | Stay put without operating lever stay put |
| Type of approach | Lateral approach, 2 directions |

Complementary

| | |
|------------------|---------------------|
| Switch actuation | From left and right |
| Positive opening | With |
| Head material | Metal |

Environment

| | |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Environmental characteristic | Standard environment |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 193 g |
| Package 1 Height | 4.6 cm |
| Package 1 width | 8.7 cm |
| Package 1 Length | 4.2 cm |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 1 |
| Package 2 Weight | 225 g |
| Package 2 Height | 15 cm |
| Package 2 width | 15 cm |
| Package 2 Length | 40 cm |
| Unit Type of Package 3 | S02 |
| Number of Units in Package 3 | 48 |
| Package 3 Weight | 9.719 kg |
| Package 3 Height | 15 cm |
| Package 3 width | 30 cm |
| Package 3 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|