# LV429287

2 CE/CD connected/disconnected position auxiliary switch - OC - for NSX100 - 630



#### Main

Range of product	NSX100250 NSX400630
Range	Compact
Product or component type	Carriage switch
Device application	Monitoring
Range compatibility	Compact - Compact NSX circuit breaker

## Complementary

Auxiliary contacts type	Standard	
Auxiliary contacts operation	CE/CD	
[Ith] conventional free air thermal current	6 A	_
[le] rated operational current	DC-12 : 6 A DC 24 V	
	DC-12: 0.6 A DC 110 V	
	AC-12: 6 A AC 50/60 Hz 110 V	
	AC-12: 6 A AC 50/60 Hz 220/240 V	
	AC-12 : 6 A AC 50/60 Hz 24 V	
	AC-12 : 6 A AC 50/60 Hz 380/440 V	
	AC-12 : 6 A AC 50/60 Hz 48 V	
	AC-12 : 6 A AC 50/60 Hz 480 V	
	AC-12 : 6 A AC 50/60 Hz 660/690 V	
	AC-15: 0.1 A AC 50/60 Hz 660/690 V	
	AC-15 : 1.5 A AC 50/60 Hz 480 V	
	AC-15 : 2 A AC 50/60 Hz 380/440 V	
	AC-15 : 4 A AC 50/60 Hz 220/240 V	
	AC-15 : 5 A AC 50/60 Hz 110 V	
	AC-15 : 6 A AC 50/60 Hz 24 V	
	AC-15 : 6 A AC 50/60 Hz 48 V	
	DC-12: 0.3 A DC 250 V	
	DC-12 : 2.5 A DC 48 V	
	DC-14: 0.03 A DC 250 V	
	DC-14: 0.05 A DC 110 V	
	DC-14: 0.2 A DC 48 V	
	DC-14:1 A DC 24 V	
Minimum load	100 mA at 24 V DC	
Quantity per set	2	

## **Environment**

#### Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0818 - Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	