



### Main

Range of product	NSX100...250 NSX400...630 NSX100...250 DC NSX400...630 DC PowerPact multistandard
Range	Compact
Product or component type	Network cable
Accessory / separate part category	Connection accessory
Range compatibility	Compact - Compact NSX circuit breaker Compact - Compact NSX DC circuit breaker PowerPact - PowerPact Multistandard circuit breaker
Device short name	Cord L = 0.35 m

### Complementary

Mounting mode	By clips
Location of connection	Inside
Connector type	RJ45
[In] rated current	0...630 A
[Ue] rated operational voltage	<= 480 V
Length	0.35 m
Product compatibility	PowerPact H-Frame PowerPact J-Frame PowerPact L-Frame

### Environment

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0818 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.