

# Figure 8

## SPK-TRP 2X 2.0 CL 1HM

Contact  
Sales  
Phone: 1300 CABLES  
olexcustomerservice@nexans.com

**Nexans Ref.:** JSF2.0CL1


**EAN 13:** 9322576337702

Two stranded bare copper conductors, PVC insulated (parallel webbed)

### DESCRIPTION

**Applications** Suitable for use in audio systems for low and high power speaker connections, security applications.

**Construction** Two stranded bare copper conductors, PVC insulated (parallel webbed) available with standard or oxygen free copper.



# Figure 8

## SPK-TRP 2X 2.0 CL 1HM

Contact  
Sales  
Phone: 1300 CABLES  
olexcustomerservice@nexans.com

### CHARACTERISTICS

#### Construction characteristics

Conductor material	Oxygen-free copper
--------------------	--------------------

#### Dimensional characteristics

Approximate weight	5.2 kg/100m
--------------------	-------------

Conductor cross-section	2 mm <sup>2</sup>
-------------------------	-------------------

Nominal Overall Size (mm)	7.0 x 3.4
---------------------------	-----------

Nominal insulation thickness	0.8 mm
------------------------------	--------

Stranding (No./mm)	64/0.20
--------------------	---------

#### Electrical characteristics

Max. DC resistance of the conductor at 20°C	10.9 Ohm/km
---	-------------

Rated Voltage U <sub>0</sub> /U	-
---------------------------------	---

Voltage drop single phase at 45°C	23.9 mV/A.m
-----------------------------------	-------------