



HOT WATER ISOLATOR KIT RANGE

SPECIFICATIONS

Codes	HWIKS, HWIKA, HWIPCU
Warranty	5 Years

PLATE SPECIFICATIONS

CODE	HWIKS / HWIKA / HWIPCU
Subplate	White
Coverplate Colour	White
Mounting	Flush Type
Installation Type	Standard flush box / 37mm Mounting block

MECH SPECIFICATIONS

CODE	HWIKS / HWIKA / HWIPCU
Rated Voltage	250V
Rated Current	20A
Type of Switch	Mechanical Rocker / Double Pole

OTHER SPECIFICATIONS

CODE	HWIKS	HWIKA	HWIPCU
Flexible Conduit Attachment at Plate	1x Straight, Clip In with locknut	1x Angle, Clip In with locknut	N/A
Flexible Conduit Attachment at Cylinder	1x Straight, Clip In with locknut	1x Straight, Clip In with locknut	N/A
Flexible Cable Attachment at Plate	N/A	N/A	PCU connection only (88PCM)
Compliance Certifications	AS/ NZ3000: 2018 and AS/NZ3133: 2013		

MECH FITTING DIMENSIONS

OTHER DIMENSIONS

CODE	HWIKS	HWIKA	HWIPCU
Padlock Shank Size	Ø 4.8-6.2mm	Ø 4.8-6.2mm	Ø 4.8-6.2mm
Padlock Hole	Ø 6.3mm	Ø 6.3mm	Ø 6.3mm
Flexible Conduit Diameter	Ø 16mm	Ø 16mm	N/A
Flexible Conduit Length	1500mm	1500mm	N/A
Load Cable Size	2.5mm ²	2.5mm ²	N/A

HWIKS Example

