



Delta DC Wallbox EV Charger

Key Features

- IEC 62196 CC52 / CHAdeMO dual charging ports
- DIN 70121 / CHAdeMO compliance
- Max. output power: 25kW
- Output voltage range: 200-500Vdc (Combo); 50-500Vdc (CHAdeMO)
- Max. 94% power efficiency
- RFID card reader for user authentication
- Network connectivity (OCPP)
- Type 3R protection and IK08 vandal-proof casing

Applications



Highway
Service



Parking



Service
Station



Workplace



Fleet



Power Input	Input Rating	(1) 208 / 240 / 277Vac; 50Hz; Single-phase / L1, L2, PE or L, N, PE (2) 400Vac; 50Hz; Three-phase / L1, L2, L3, N, PE
	Power Factor	> 0.98
	Current THD	Compliant with IEEE 519
	Efficiency	94%
Power Output	DC Output #1	IEC 62196 (type 2) DC Level 2, 200-500 Vdc, 65 A max., 25kW max.
	DC Output #2	CHAdEMO, 50-500 Vdc, 60A max., 25 kW max.
Protection	Protection	Over current, Under voltage, Over voltage, Residual current, Surge protection, Short circuit, Over temperature, Ground fault
User Interface & Control	Display	2.7" OLED screen
	Support Language	English (Other languages available upon request)
	Push Buttons	Multi-functional buttons (LED light: Orange, Blue) / Emergency stop button (Red)
	Charge Options	Charge options to be provided upon request: Charge by duration, Charge by energy
	User Authentication	ISO/IEC 14443 Type A/B RFID for user authentication
Communication	Network Interface	Ethernet (standard); 3G (optional); Wifi (optional)
Environmental	Operating Temperature	-22 °F to +122 °F (-30 °C to +50 °C)
	Storage Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
	Humidity	< 95% relative humidity, non-condensing
	Altitude	Up to 6500 ft. (2000 m)
Mechanical	Ingress Protection	Type 3R
	Enclosure Protection	IK08 according to IEC 62262
	Cooling	Forced air
	Charging Cable Length	13 ft. (4 m)
	Dimension (W x H x D) / Weight	27 x 17 x 9 in. (680 x 430 x 230 mm) 104 lbs (47kg), excluding plug and cable
Regulation	Certificate	UL, cUL, UL 2202, UL 2231
Compatibility	Compatible vehicle brands	CCS: GM, Ford, BMW; CHAdEMO: Nissan, Toyota, Mitsubishi, Tesla (via adapter)

Specifications are subject to change without notice.



YHI (NEW ZEALAND) LTD
A subsidiary of YHI International Limited

**Preferred Delta Quality Partner:
YHI (New Zealand) Ltd**

T: +64 9 250 0000 **F:** +64 9 279 2452

E: powersystems@yhi.co.nz

W: www.powersystems.co.nz

W: www.yhipower.co.nz

